



EQUILEX CHEMICALS BV
Jan van Galenstraat 54
3115 JG SCHIEDAM
The Netherlands

Tel : + 31 10 340 30 90
www.equilex.com
info@equilex.com

SALES SPECIFICATION

Ref.no: S_SOL-150ND_GI
Rev.no: 00
Date: 02/05/2024

INDUSTRIAL SOLVENT 150ND (Solvent Naphtha 150ND) Grade GI

PROPERTY	UNITS	SPECIFICATION	TYPICALS	TEST METHOD
Appearance	--	Clear to very slight pale liquid free from sediments	Clear liquid free from sediments	Visual
Color	-	20 Max	5	Apha
Density @ 15°C	gm/ml	0.88-0.905	0.884	ASTM D 4052
Flash Point - PMCC	°C	63 Min	66	ASTM D 93
Naphthalene Content	%	0.9 Max	0.38	HPLC-GC
Sulphur Content	ppm	5 Max	<1	ASTM D 5453
Aromatic content	%	99 Min	99.9	ASTM D 1319
Boiling Range	°C			ASTM D 86
IBP		175 Min	181	
FBP		210 Max	202	

Disclaimer of Liability

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Equilex BV's control. Equilex BV disclaims any liability in connection with the use of the information which is illustrative only and does not warrant against infringement by reason of the use of any of its products in combination with other material or any process.