

EQUILEX CHEMICALS BV

Jan van Galenstraat 54 3115 JG SCHIEDAM The Netherlands

Tel: + 31 10 340 30 90 www.equilex.com info@equilex.com

SALES SPECIFICATION

Ref.no: S_SOL-200ND_GI

Rev.no: 00

Date: 02/05/2024

(Solvent Naphtha 200ND)

Grade GI

| PROPERTY | UNITS | SPECIFICATION | TYPICALS | TEST METHOD |
|---------------------|-------|------------------------------------|------------------------------|-------------|
| Appearance | | White to Pale yellow, clear liquid | Pale yellow, clear liquid | Visual |
| Color | - | 1.0 Max | 0.5 | ASTM D 1500 |
| Density @ 30°C | g/cc | 0.99 Max | 0.9828 | ASTM D 4052 |
| Flash Point - PMCC | °C | 94 Min | 104 | ASTM D 93 |
| Naphthalene Content | % | 0.9 Max | 0.583 | HPLC-GC |
| Sulphur Content | ppm | 5 Max | <1 | ASTM D 5453 |
| Aromatic content | % | 98 Min | 99 | ASTM D 1319 |
| Boiling Range | °C | | | ASTM D 86 |
| IBP | | 220 Min | 244 | |
| FBP | | 310 Max | 302 | |

Disclaimer of Liability

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Equilex BV's control. Equilex BV disclaims any liability in connection with the use of the information which is illustrative only and does not warrant against infringement by reason of the use of any of its products in combination with other material or any process.