



EQUILEX CHEMICALS BV
Jan van Galenstraat 54
3115 JG SCHIEDAM
The Netherlands

Tel : + 31 10 340 30 90
www.equilex.com
info@equilex.com

SALES SPECIFICATION

Ref.no: S_WOIL_GIH
Rev.no: 00
Date: 30/09/2023
Origin: India

WASH OIL Grade GIH

PROPERTY	UNITS	SPECIFICATION	TYPICALS	TEST METHOD
Appearance	--	Clear Liquid, yellow	Clear liquid, Pale yellow	Visual
Color		1.5 to 3	1.5 +	ASTM D 1500
Density @ 30°C	gm/ml	0.975 – 1.00	0.986	ASTM D 4052
Flash Point	°C	93 Min	105	ASTM D 93
Aromatic content	%	95 Min	99.1	ASTM D 6729
K. viscosity @ 37.8°C	Cst	4.5 – 5.5	5.2	ASTM D 445
Boiling Range	°C			ASTM D 86
Initial Boiling Point		230 Min	247	
Dry Point		360 Max	352	
Gum content	mg/100ml	50 Max	28.3	ASTM D 381
Sulphur Compound	ppm	1 - 50	10.3	ASTM D 5453

Disclaimer of Liability

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Equilex BV's control. Equilex BV disclaims any liability in connection with the use of the information which is illustrative only and does not warrant against infringement by reason of the use of any of its products in combination with other material or any process.