

EQUILEX CHEMICALS BV Jan van Galenstraat 54 3115 JG SCHIEDAM The Netherlands

Tel : + 31 10 340 30 90 www.equilex.com info@equilex.com

SALES SPECIFICATION

Ref.no: S_WOIL_GIL Rev.no: 01 Date: 30/09/2023

WASH OIL Grade GIL

PROPERTY	UNITS	SPECIFICATION	TYPICALS	TEST METHOD
Appearance		Clear Liquid	Clear liquid, very slightly Pale	Visual
Color		0.0 to 0.5	0.0 +	ASTM D 1500
Density @ 30°C	gm/ml	0.88 – 0.93	0.896	ASTM D 4052
Flash Point	°C	64 Min	72	ASTM D 93
Aromatic content	%	95 Min	99.993	ASTM D 6729
K. viscosity @ 37.8°C	Cst	1.5 – 2.5	1.97	ASTM D 445
Boiling Range Initial Boiling Point Dry Point	°C	175 Min 230 Max	186 228	ASTM D 86
Gum content	mg/100ml	5 Max	3.8	ASTM D 381
Sulphur Compound	ppm	1 - 50	6.2	ASTM D 5453

Disclaimer of Liability

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Equilex BV's control. Equilex BV disclaims any liability in connection with the use of the information which is illustrative only and does not warrant against infringement by reason of the use of any of its products in combination with other material or any process.