



EQUILEX CHEMICALS BV
Jan van Galenstraat 54
3115 JG SCHIEDAM
The Netherlands

Tel : + 31 10 340 30 90
www.equilex.com
info@equilex.com

SALES SPECIFICATION

Ref.no: S_WOIL_GIM
Rev.no: 01
Date: 30/09/2023

WASH OIL Grade GIM

PROPERTY	UNITS	SPECIFICATION	TYPICALS	TEST METHOD
Appearance	--	Clear Liquid, pale yellow	Clear liquid, slightly Pale yellow	Visual
Color		0.5 to 1	0.5 +	ASTM D 1500
Density @ 30°C	gm/ml	0.94 – 0.975	0.968	ASTM D 4052
Flash Point	°C	85 Min	93	ASTM D 93
Aromatic content	%	95 Min	99.92	ASTM D 6729
K. viscosity @ 37.8°C	Cst	2.5 – 4.5	3.7	ASTM D 445
Boiling Range Initial Boiling Point Dry Point	°C	210 Min 290 Max	218 280	ASTM D 86
Gum content	mg/100ml	25 Max	16	ASTM D 381
Sulphur Compound	ppm	1 - 50	8.9	ASTM D 5453

Disclaimer of Liability

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Equilex BV's control. Equilex BV disclaims any liability in connection with the use of the information which is illustrative only and does not warrant against infringement by reason of the use of any of its products in combination with other material or any process.